

# APC-9210



21.5", Capacitive Touch Screen, android 10, Multi-Touch Android Panel PC



## Features

- 21.5" LED backlight LCD and P-Cap Multi-Touch Panel
- Front Panel IP65
- Rockchip RK3399, ARM 2xCortex-A72+4xCortex-A53 1.8GHZ
- Panel and VESA Mounting



## Specifications

| System            |  | Audio                    |   |
|-------------------|--|--------------------------|---|
| CPU               | Rockchip RK3399, ARM 2xCortex-A72+4xCortex-A53 1.8GHZ                            | Audio                    | 1 x Line-out 1 x Line-in                                  |
| GPU               | Mali-T860 GPU MP4 GPU  | Speaker                  | 2 x Speaker (Optional)                                    |
| Memory            | DDR3 4GB   | Wireless                 |   |
| Storage           | EMMC 16G/32G   | WIFI                     | 2.4GHz/5GHz   |
| Operating System  | Android 10   | M.2                      | M.2 3042 for 4G ; M.2 3052 for 5G ;                       |
| Display           |  | Power Specification      |   |
| Size              | 21.5-inch  | Power Input              | 9~36V   |
| Resolution        | 1920 x 1080  | Power Adapter            | AC-DC, 12V@5A, 60W  |
| Viewing Angle     | 89/89/89/89  | Power Consumption        | 18W(Typ.)   |
| Color Support     | 16.7M  | Environment              |   |
| Brightness        | 250 cd/m²  | Operating Temperature    | -10~50°C  |
| Contrast Ratio    | 3000:1   | Storage Temperature      | -20~60°C  |
| Response Time     | 20/5 (Typ.)(Tr/Td) ms  | Relative Humidity        | 10%-90%,@ 40°C (non-condensing)                           |
| Backlight         | LED  | Vibration                | 5~500Hz, 0.026 G²/Hz, 2.16 Grms, X, Y, Z, 1 hour per axis |
| Backlight Life    | 40000h   | Certifications           | CE, FCC   |
| Touch screen      |  | Physical Characteristics |   |
| Type              | Projection multi touch capacitive touch screen                                   | Hoasing                  | Aluminum alloy panel, all-metal structure                 |
| Control Interface | USB  | Mounting Mode            | Panel-mount, VESA-mount                                   |
| Surface Hardness  | ≥6H  | Dimension (W x L x H)    | 528.3 x 326.1 x 53.3 mm                                   |
| Transmittance     | 85%  | Weight                   | 5.45Kg  |
| I/O Connectors    |  |                          |   |
| Serial Port       | 1x RS-232  |                          |   |
| USB Port          | 4 x USB3.0   |                          |   |
| Ethernet          | 2 x GbE LAN  |                          |   |
| GPIO              | 1 x GPIO (Optional)  |                          |   |
| Others            | 1 x DC-IN (3-Pin Phoenix)<br>1 x Remote switch connector<br>1 x ATX Power Switch |                          |   |

## Dimension

